

# FLINDT GARDEN BOLLARD


, , Designed by Christian Flindt

Type:

Product:

Project:

Modified:



## Technical specifications

### Materials

Top/Base plate: die-cast aluminum.  
Post: extruded aluminum.

### Finishes

Textured, powder coated paint in Natural Aluminum, Corten, or Black.

### Mounting

The bollard requires a separate, 24V or 230V DC power supply.

Flindt Garden with an integrated driver (230V) is available with a baseplate and anchor mounting. A mounting fixture is available as a spare part.

Flindt Garden without an adapter (24V) must be connected to an external adapter. The adapter must be brought separately. A maximum of 6 Garden bollards (6,5 W) can be run by one adapter.

The maximum distance to the last bollard is 30 m. Stem: Ø50 mm.

Spike mounted bollard(Plug&Play): For use in soil or gravel; includes weather-proof cables and connectors for above-ground runs.

Anchor mounted bollard(certified electrician): for casting in new concrete pad.

Base mounted bollard(certified electrician): Includes baseplate for anchoring to decks and floors.

### Information

#### Electrical:

System Wattage: 6.5-8.8W

LED Wattage: 6.0W

Delivered lumens: 215-291 lm

Efficacy: 24.1 - 44.7 lm/W

#### Certifications:

cULus, Wet Location

Protection class IP65

IK class 06

BUG Rating: B0-U2-G0

Color Rendering: Ra≥80

LED is non-dimming.

Low Voltage power supply 24VDC is remote mounted for multiple bollards per supply. Spike mounted bollards use provided weather-proof cables and connectors for above-ground runs. Plug and play. Anchor or Base mounted bollards: installation determined by certified electrician with below ground cabling and conduit. Consult factory for remote power supply information; maximum bollards and cable distances. For the E-socket product variants, bulbs are not included. LED light source is part of the product.

---

# FLINDT GARDEN BOLLARD

, , Designed by Christian Flindt

---

Anchor or Base mounted bollards: installation determined by certified electrician with below ground cabling and conduit. For mounting instructions, see download section on the product detail page.

---

# FLINDT GARDEN BOLLARD

, , Designed by Christian Flindt

## Variant Options

For particular variant options, please check our online Product Variants Configurator on the product detail page.

VARIANT NO.	LIGHT SOURCE	VOLTAGE/FRQ	DELIVERED LUMEN	FEATURES	CABLE	COLOR, RAL	W / H / L (IN) / W (LB)
10000158330	Integrated LED 3000K (7 W, no bulb required)	24V	252	-	-	NAT PAINT ALU, 162	- / - / - in / 5.2 lb
10000158331	Integrated LED 3000K (7 W, no bulb required)	24V	215	-	-	CORTEN COLOR, 954	- / - / - in / 5.2 lb
10000158334	Integrated LED 2700K (7 W, no bulb required)	24V	252	-	-	NAT PAINT ALU, 162	- / - / - in / 5.2 lb
10000158335	Integrated LED 2700K (7 W, no bulb required)	24V	215	-	-	CORTEN COLOR, 954	- / - / - in / 5.2 lb
10000158336	Integrated LED 3000K (7 W, no bulb required)	24V	252	-	-	NAT PAINT ALU, 162	- / - / - in / 5.2 lb
10000158337	Integrated LED 3000K (7 W, no bulb required)	24V	215	-	-	CORTEN COLOR, 954	- / - / - in / 5.2 lb
10000158340	Integrated LED 2700K (7 W, no bulb required)	24V	252	-	-	NAT PAINT ALU, 162	- / - / - in / 5.2 lb
10000158341	Integrated LED 2700K (7 W, no bulb required)	24V	215	-	-	CORTEN COLOR, 954	- / - / - in / 5.2 lb
5747402474	Integrated LED 3000K (7 W, no bulb required)	24V	215	-	-	CORTEN COLOR, 954	- / - / - in / 2.8 lb
5747402487	Integrated LED 2700K (7 W, no bulb required)	24V	215	-	-	CORTEN COLOR, 954	- / - / - in / 2.8 lb
5747402500	Integrated LED 3000K (7 W, no bulb required)	24V	215	-	-	CORTEN COLOR, 954	- / - / - in / 3.2 lb
5747402513	Integrated LED 2700K (7 W, no bulb required)	24V	215	-	-	CORTEN COLOR, 954	- / - / - in / 5.2 lb
5747402568	Integrated LED 3000K (7 W, no bulb required)	24V	215	-	-	CORTEN COLOR, 954	- / - / - in / 2.9 lb
5747402571	Integrated LED 2700K (7 W, no bulb required)	24V	215	-	-	CORTEN COLOR, 954	- / - / - in / 2.9 lb
5747402597	Integrated LED 3000K (7 W, no bulb required)	24V	215	-	-	CORTEN COLOR, 954	- / - / - in / 3.4 lb
5747402607	Integrated LED 2700K (7 W, no bulb required)	24V	215	-	-	CORTEN COLOR, 954	- / - / - in / 5.4 lb
5747402830	Integrated LED 3000K (7 W, no bulb required)	24V	252	-	-	NAT PAINT ALU, 162	- / - / - in / 2.8 lb
5747402843	Integrated LED 2700K (7 W, no bulb required)	24V	252	-	-	NAT PAINT ALU, 162	- / - / - in / 2.8 lb
5747402869	Integrated LED 3000K (7 W, no bulb required)	24V	252	-	-	NAT PAINT ALU, 162	- / - / - in / 5.2 lb
5747402872	Integrated LED 2700K (7 W, no bulb required)	24V	252	-	-	NAT PAINT ALU, 162	- / - / - in / 3.2 lb
5747402924	Integrated LED 3000K (7 W, no bulb required)	24V	252	-	-	NAT PAINT ALU, 162	- / - / - in / 2.9 lb
5747402937	Integrated LED 2700K (7 W, no bulb required)	24V	252	-	-	NAT PAINT ALU, 162	- / - / - in / 2.9 lb
5747402953	Integrated LED 3000K (7 W, no bulb required)	24V	252	-	-	NAT PAINT ALU, 162	- / - / - in / 3.4 lb
5747402966	Integrated LED 2700K (7 W, no bulb required)	24V	252	-	-	NAT PAINT ALU, 162	- / - / - in / 3.4 lb
5747405536	Integrated LED 3000K (no bulb required)	24V	-	-	-	NAT PAINT ALU, 162	2 / 27.4 / 2 in / 4.5 lb
5747405549	Integrated LED 2700K (no bulb required)	24V	-	-	-	NAT PAINT ALU, 162	27.5 / 2 / 2 in / 4.8 lb
5747405565	Integrated LED 3000K (no bulb required)	24V	-	-	-	NAT PAINT ALU, 162	2 / 13.6 / 2 in / 4.5 lb
5747405578	Integrated LED 2700K (no bulb required)	24V	-	-	-	NAT PAINT ALU, 162	2 / 13.6 / 2 in / 4.5 lb
	Integrated LED 3000K (no bulb required)					CORTEN	27.5 / 2 / 2 in / 4.8

# FLINDT GARDEN BOLLARD

, , Designed by Christian Flindt

5747405594	required)	24V	-	-	COLOR, 954	lb	
5747405604	Integrated LED 2700K (no bulb required)	24V	-	-	CORTEN COLOR, 954	27.5 / 2 / 2 in / 4.5 lb	
5747405617	Integrated LED 4000K (no bulb required)	24V	-	-	CORTEN COLOR, 954	2 / 13.6 / 2 in / 2.6 lb	
5747405620	Integrated LED 3000K (no bulb required)	24V	-	-	CORTEN COLOR, 954	2 / 13.6 / 2 in / 4.5 lb	
5747405633	Integrated LED 2700K (no bulb required)	24V	-	-	CORTEN COLOR, 954	13.6 / 2 / 2 in / 4.5 lb	
5747408782	Integrated LED 3000K (7 W, no bulb required)	24V	-	With cord	BLK, 731	2 / 13.6 / 2 in / 3.2 lb	
5747408795	Integrated LED 2700K (7 W, no bulb required)	24V	-	With cord	BLK, 731	2 / 13.6 / 2 in / 3.2 lb	
5747408818	Integrated LED 3000K (7 W, no bulb required)	24V	-	With cord	BLK, 731	2 / 27.5 / 2 in / 4.0 lb	
5747408821	Integrated LED 2700K (7 W, no bulb required)	24V	-	With cord	BLK, 731	2 / 27.5 / 2 in / 4.0 lb	
5747408847	Integrated LED 3000K (7 W, no bulb required)	24V	200	-	With cord	BLK, 731	- / - / - in / 2.1 lb
5747408850	Integrated LED 2700K (7 W, no bulb required)	24V	200	-	With cord	BLK, 731	- / - / - in / 2.1 lb
5747408876	Integrated LED 3000K (7 W, no bulb required)	24V	200	-	With cord	BLK, 731	- / - / - in / 2.2 lb
5747408889	Integrated LED 2700K (7 W, no bulb required)	24V	200	-	With cord	BLK, 731	- / - / - in / 2.2 lb
5747408902	Integrated LED 3000K (7 W, no bulb required)	24V	200	-	-	BLK, 731	2 / 13.7 / 2 in / 3.1 lb
5747408915	Integrated LED 2700K (7 W, no bulb required)	24V	200	-	-	BLK, 731	13.7 / 2 / 2 in / 3.1 lb
5747408931	Integrated LED 3000K (7 W, no bulb required)	24V	200	-	With cord	BLK, 731	- / - / - in / 2.9 lb
5747408944	Integrated LED 2700K (7 W, no bulb required)	24V	200	-	With cord	BLK, 731	- / - / - in / 2.9 lb
5747408960	Integrated LED 3000K (7 W, no bulb required)	24V	200	-	With cord	BLK, 731	- / - / - in / 3.1 lb
5747408973	Integrated LED 2700K (7 W, no bulb required)	24V	200	-	With cord	BLK, 731	- / - / - in / 3.1 lb
5747408999	Integrated LED 3000K (7 W, no bulb required)	24V	200	-	-	BLK, 731	27.5 / 2 / 2 in / 3.9 lb
5747409008	Integrated LED 2700K (7 W, no bulb required)	24V	200	-	-	BLK, 731	27.5 / 2 / 2 in / 3.9 lb