

PH 2/1 PENDANT

, , Designed by Poul Henningsen

Type:

Product:

Project:

Modified:



Technical specifications

Materials

Shades: Handblown white opal glass (sandblasted on the undersides for uniform light distribution). Suspension: Black metalized or high lustre chrome plated, spun aluminum.

Finishes

Black metalized or high lustre chrome plated. White opal glass.

Mounting

Canopy: White. Cord type: 3-conductor, 18 AWG black PVC power cord. Cord length: 12'. For mounting instructions, see download section on the product detail page.

Information

Electrical:

System Wattage: 10W

LED Wattage: 9 W

Delivered lumens: 286

Efficacy: 28.6 lm/W

Certifications:

cULus, Dry Location

Protection class IP20

Controllability: Phase dimming

Actual performance dependent upon screw-base lamp used. For the E-socket product variants, bulbs are not included. LED light source is part of the product.

PH 2/1 PENDANT

, , Designed by Poul Henningsen

Variant Options

For particular variant options, please check our online Product Variants Configurator on the product detail page.

VARIANT NO.	LIGHT SOURCE	VOLTAGE/FRQ	DELIVERED LUMEN	FEATURES	CABLE	COLOR, RAL	W / H / L (IN) / W (LB)
5741925300	1 × G16.5 bulb (candelabra base) (20 W max)	120V/60HZ	286	-	Black fabric cord	BLACK METALIZED, 906	7.9 / 5.5 / 7.9 in / 2.1 lb
5741925575	1 × G16.5 bulb (candelabra base) (20 W max)	120V/60HZ	286	-	White fabric cord	Brass metallised	7.9 / 5.5 / 7.9 in / 2.1 lb
5741925588	1 × G16.5 bulb (candelabra base) (20 W max)	120V/60HZ	286	-	Black fabric cord	HIGH LUSTRE CHROME PLATED, 900	7.9 / 5.5 / 7.9 in / 2.1 lb
