PH 2/1 PORTABLE LAMP

, , Designed by Poul Henningsen

Type:	
Product:	
Project:	
Modified:	



Technical specifications

Materials

Shades: Mouth-blown white opal glass.

Top plate, base and stem: Brass metallised or High lustre chrome plated aluminium.

Finishes

Brass metallised or high lustre chrome plated. White opal glass.

Mounting

1.5 m. USB-A/USB-C cord.

Light control: Switch on base.

White light indicator on base when charging.

Batteries: Lipo, rechargeable, replaceable.

Battery lifetime: 5.5 hours at 100%.

Dim-2-Warm (1800-2700K) Stepless-dim and 4 step-dim (5%, 20%, 45%, 100%) customer user setting (can switch between the functions). For mounting instructions, see download section on the product detail page.

Information

Please note that the PH 2/1 Portable comes with a USB-cord but without an adaptor. Please use a 15W/3A USB adaptor. For the Esocket product variants, bulbs are not included. LED light source is part of the product.

PH 2/1 PORTABLE LAMP

, , Designed by Poul Henningsen

Variant Options

For particular variant options, please check our online Product Variants Configurator on the product detail page.

VARIANT NO.	LIGHT SOURCE	VOLTAGE/FRQ	DELIVERED LUMEN	FEATURES	CABLE	COLOR, RAL	W / H / L (IN) / W (LB)
5744170424	Integrated LED 2700K-1800K dim-2-warm (4 W, no bulb required)		289	-	Without cord	Brass metallised	200 / 360 / 200 in / 1.3 lb
5744170437	Integrated LED 2700K-1800K dim-2-warm (4 W, no bulb required)		289	-	Without cord	HIGH LUSTRE CHROME PLATED, 900	200 / 360 / 200 in / 1.3 lb