

# PH 4/3 PENDANT

, , Designed by Poul Henningsen

Type:

Product:

Project:

Modified:



## Technical specifications

### Materials

Shades: Spun aluminum.

### Finishes

White, powder coated.

### Mounting

Canopy: White. Cord type: 3-conductor, 18 AWG white PVC power cord. Cord length: 12'. For mounting instructions, see download section on the product detail page.

### Information

#### Electrical:

System Wattage: 15W

LED Wattage: 14 W

Delivered lumens: 414

Efficacy: 27.6 lm/W

#### Certifications:

cULus, Dry Location

Protection class IP20

Controllability: Phase dimming

Actual performance dependent upon screw-base lamp used. For the E-socket product variants, bulbs are not included. LED light source is part of the product.

---

# PH 4/3 PENDANT

, , Designed by Poul Henningsen

---

## Variant Options

For particular variant options, please check our online Product Variants Configurator on the product detail page.

VARIANT NO.	LIGHT SOURCE	VOLTAGE/FRQ	DELIVERED LUMEN	FEATURES	CABLE	COLOR, RAL	W / H / L (IN) / W (LB)
5741928598	1 × A-19 bulb (medium base) (15 W max)	120V/60HZ	414	-	White fabric cord	WHITE CLASSIC MATTE, 020	15.7 / 7.9 / 15.7 in / 2.7 lb

---