

# TOLDBOD 155 OUTDOOR WALL LAMP

, , Designed by Louis Poulsen A/S

Type:	<input type="text"/>
Product:	<input type="text"/>
Project:	<input type="text"/>
Modified:	<input type="text"/>



## Technical specifications

### Materials

Shield: Tempered sand blasted glass. Wall plate: Die cast aluminum. Luminaire head: Die cast aluminum. Arm: Extruded aluminum.

### Finishes

Black or natural painted aluminum, powder coated.

### Mounting

Surface: Mounted directly to finished surface over a recessed 4" octagonal junction box. For mounting instructions, see download section on the product detail page.

### Information

#### Electrical:

System Wattage: 10 W  
Delivered lumens: 189 lm  
Efficacy: 18.9 lm/W

#### Certifications:

cULus, Wet Location  
Protection class IP44  
IK class 05

BUG Rating: B1-U2-G1

Controllability: Phase dimming

Min.-Max. Ambient Temp: -20°C to +40°C

Actual performance dependent upon screw-base lamp used. For the E-socket product variants, bulbs are not included. LED light source is part of the product.

---

# TOLDBOD 155 OUTDOOR WALL LAMP

, , Designed by Louis Poulsen A/S

---

## Variant Options

For particular variant options, please check our online Product Variants Configurator on the product detail page.

VARIANT NO.	LIGHT SOURCE	VOLTAGE/FRQ	DELIVERED LUMEN	FEATURES	CABLE	COLOR, RAL	W / H / L (IN) / W (LB)
5743911723	1 × G16.5 bulb (candelabra base) (10 W max)	120V/60HZ	2093	-	-	NAT PAINT ALU, 162	6.1 / 6.2 / 10.5 in / 2.6 lb
5743911736	1 × G16.5 bulb (candelabra base) (10 W max)	120V/60HZ	2093	-	-	BLK, 723	6.1 / 6.2 / 10.5 in / 2.6 lb

---